

U/PRTS

10/525097

DT01 Rec'd PCT/PTC 17 FEB 2005

## A Device for Electrode Positioning

### BACKGROUND OF THE INVENTION

The present invention relates to a device for electrode (as herein defined) positioning for extra cellular recording (hereafter called "electrode positioning device") of cell activity of the brain and of the nervous system of a human or an animal body, (hereinafter called "brain"). The electrodes are preferably positioned in the XYZ planes for collecting and recording the signals of the cell activity. This activity is afterwards amplified, filtered, sorted and acquired into an acquisition system like a computer memory.

The positioning of the electrodes is important for reaching a specific target in the brain for diagnostic, research and even healing purposes, e.g. for extra cellular recording from the brain and the nervous system as well as in functional neurosurgery. Such electrode positioning devices are known. They consist essentially of a base or an adapter, for positioning the electrodes in the XY plane as well as in a system for positioning them in the Z plane (mounted upon same in a stable manner and connecting means both to the brain and to the signal recording device). This device is mechanically connected so that it can reach the target in the brain from one end and connected to the signal conditioning system on the other end.

There are known many such devices. Most of them have many advantages. However all the known devices have two main disadvantages which make them unsatisfactory in the use thereof. Such devices are, for example:

1. The Alpha Omega System - EPS
2. The Thomas Recording System - Eckhorn
3. The FHC System - Micro Step Multi Drive system

All these systems have the following disadvantages:

- The positioning of the electrodes individually in the XY plane is very complicated and expensive. For each layout of the electrodes a special device is needed with a suitable layout of holes.
- The number of channels/electrodes that can be effectively used at once is limited to 32 or less.

It has thus been desirable to develop an electrode positioning device which does not have said disadvantages. Said device should be easy to manufacture and use and not be too expensive.

### **SUMMARY OF THE INVENTION**

The present invention thus consists in an electrode positioning device (as herein defined) which consists in a base which is to be connected to the brain directly or indirectly using a remote adapter, on said base being mounted directly or indirectly movable terminal holders on which holders extend guides, on which guides extend movable means which means hold the guiding tubes (as well called tubes) and the electrodes, said electrodes being actuated by suitable actuating means.

The guides may be tubes, rods and the like.

The movable means may be conveyer, tubes and the like.

The base may sit on a chamber, a stereotactic frame, a robot's arm or any other suitable adaptation arrangement. The base may be round, rectangular, arc or have any other suitable geometry, but the round shape is preferred. The base may comprise a groove or any other suitable arrangement for adapting a moving cartridge

that comprises the terminal holder or the groove or the suitable arrangement may comprise the terminal holder without using a cartridge.

In the device according to the present invention, the user works preferably with a multi-channel system with the possibility to position each electrode or group of  
5 electrodes in the XYZ planes individually and independently.

A chamber or well, if present, may be a part of the device according to the present invention, or the device may also be connected by a remote adapter to the brain.

The electrode in connection with the present invention may be a  
10 microelectrode or macro-electrode etc. However, the electrode in connection with the present invention may be a probe, an injection needle or any other suitable component that may be used with the system. The Electrode Guiding tube is preferably made in a special manner, i.e. with a bend feature in order to enable the electrodes/probes to get near each other. More than one electrode may be inserted  
15 into a tube in order to increase the number of channels. More than one tube is advantageously mounted in the same terminal.

As indicated above, in an advantageous embodiment of the present invention a base with a special geometry is designed. A cartridge is preferably located within a groove or in any other suitable form in the base. This cartridge comprises the  
20 terminal holder, which holder may move inside the channel toward the center of the base and backward, while the cartridge moves around the center of the base. These moves enable the user to take the electrodes to any required position within the working range.

When the maximum number of terminals is used the cartridge can no longer move because there is no place for such movement. In this case the cartridge is cancelled and the base itself is made to accommodate the terminal holders.

5 All required layouts of the electrodes can be reached because the terminal can move toward the center and backward and also be rotated around its center and around the center of the base. The holders of the electrodes and of the tubes do not prevent the tubes to get near each other because the outer tubes (The Electrode Guiding tube) are advantageously bent.

10 The terminal may be connected to the base terminal holder by a ball joint.

The terminal may be made round or rectangular. It advantageously includes two holders inside it. Each holder includes a thread and is screwed to a threaded rod inside the tube. The holders may have a special geometry. One holder holds the guiding tube (tubing holder) – and moves it up and down. The second holder holds  
15 the electrode (electrode holder) and moves it up and down. Each holder moves up and down when rotating the threaded rod that is connected to it. In order to enable to have one terminal for both holders, the terminal should accommodate two screws therefore each holder preferably includes two holes one threaded and one simple. Opposite the simple hole in one holder there is a threaded hole in the second holder.

20 The terminal may be rotated around its axes in order to achieve extra flexibility in the XY positioning. The terminal is preferably installed on the terminal holder by closing a lock knob or by a ball joint or any other adapting mean. The terminal itself may be mounted on a stereotactic frame or other suitable adaptation arrangement and may be used as an independent system by attaching the proper adaptation arrangement

to its base. Additional way to move the holders as a replacement for the threaded rods could be a telescopic tube or a hydraulic piston. Or other pushing mean.

The terminals may be arranged in various positions, each being distanced differently from the center of the base and individually being located in the XYZ  
5 plane.

The actuating means in the Z direction may be electrical ones, e.g. a motor; hydraulic ones and even manual ones.

The moment the electrical or hydraulic means for actuating in the Z direction, are no longer required, they may be removed and the device may be covered by a  
10 suitable cover. This possibility is also within the scope of the present invention.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

These and further features and advantages of the invention will become more clearly understood in the light of the ensuing description of a preferred embodiment thereof, given by way of example only, with reference to the  
15 accompanying drawings, wherein-

Figure 1 shows a perspective view of the device according to the present invention;

Figure 2 shows a perspective view of a base being part of the device shown in Figure 1;

20 Figure 3 shows a perspective view of the base shown in Figure 2 connected to a chamber which is in turn connected to a brain;

Figure 4 shows a perspective view of a terminal;

Figure 5 shows a perspective view of a terminal holder;

Figure 6 shows a perspective view of a cartridge;

Figure 7 shows a perspective view of a base being part of another embodiment of the device according to the present invention which base does not comprise any cartridge;

Figure 8 shows a perspective view of a device having a base according to

5 Figure 7;

Figure 9 shows a perspective view of a manual device according to the present invention in which the electrodes are positioned in various distances from the center;

Figure 10 shows a perspective view of a device where the terminals are  
10 independently used and adapted on a special adaptation arrangement.  
and

Figure 11 shows a schematic view of an electric signal transmitting device according to the present invention being connected at one end to the brain and at the second end to a device for recording cell activity.

## 15 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Figure 1 comprises base 1, groove 2, in which move cartridges 3. On said cartridge 3 is mounted terminal holder 4 which holds terminal 5, in which extend electrode holder 11 and tube holder 17. To the other end of terminal holders 5 are connected by way of shaft connector 6, Shafts (cables) 7 which in turn are connected  
20 to engine 8 (for the sake of clarity there are referenced only one, cartridge 3, terminal holder 4, screw 6 and cable 7). Terminal holders 4 may move forward and backward in cartridges 3, which cartridge 3 in turn may move in groove 2 and around base 1. Figure 1 shows a device with only 5 terminals by way of example. It is connected to the motor with a remote control shaft 7 The motor and shafts may be removed in

order to install a cover. A system without the motors and shafts may be used as a manual system.

Figure 2 shows base 1 comprising groove 2 having an opening 9 to be  
5 mounted on the chamber 10 or other mechanical adaptation arrangement. (not shown).

Figure 3 shows base 1 shown in Figure 2 sitting on chamber 10 mounted on opening 9. Chamber 10 sits on the brain or on another mechanical adaptation arrangement.

10 Figure 4 shows a detail of terminal 5 comprising tube holder 11 and electrode holder 12. Said terminal 5 is mounted on a terminal holder 4 (not shown) and terminates with shaft connector 6.

Figure 5 shows a terminal holder comprising holes 13 and 14. Hole 13 is connected to a lock knob that locks terminal 5 and hole 14 is connected to a screw  
15 that moves the terminal holder toward the center of the base and backward.

Figure 6 shows cartridge 3 in which is seen channel 15 in which terminal holder 4 can move.

Figure 7 shows base 16 in which are located channels 17 and opening 18. In channels 17 can move terminal holders 4 forward and backward. Opening 18 is  
20 sitting on the brain or a chamber or a mechanical adaptation arrangement.(not shown).

Figure 8 shows another perspective view of the embodiment of the present invention which does not comprise any cartridge. Said embodiment comprises base 16, channels 17 (not seen clearly), terminals 5 and screws 19.

Figure 9 shows a device in which terminals 5 can move with terminal holder 4 on cartridge 3 which can move in groove 2 around the center of base 1

Figure 10 shows terminal 5 with special adaptation 20 which may be adapted on a chamber or stereotactic frame or other adaptation.(not shown)

5        Figure 11 describes the different stages in the micro recording procedure of brain activity. In this procedure the user inserts electrodes into the brain and records cell activity.

10        The first system in the setup is the electrode manipulator. This manipulator sits on the brain (in some cases it does not sit on the brain but it is holed away from it). The procedure is performed in the following stages:

Stage #1: Head stage – amplifier for first stage amplification of the signal.

Stage #2: signal conditioning – further amplification and filtering of the signal.

15        Stage #3: spike sorting – the spikes are sorted according to shape, amplitude or other specifications. This sorting could be done in real time during the recording procedure or it also could be done after the experiment.

Stage #4: Data acquisition – in this stage the signal is acquired for post processing.

20        Stage #5: Post processing – in addition to the spike sorting in stage #3, a finer sorting could be done.

The schematic view shown in Figure 11 shows device 21 according to the present invention being connected at one end to brain 22 and on the other hand to micro-recording device 23.